

Fig1




Fig2




Fig3




Fig4

Type	Fig. No	Main Dimensions(mm)					Dry withstand voltage kV	Wet withstand voltage kV	Puncture voltage kV	Mechanical strength kN	Packing	
		A	B	D	d	R					No.per	Mass(kg)
S.03	1	57	63	35	11	5	17	8	25	6,25	100	23
S.05	1	75	88	41	17	8	22	11	33	17,80	24	16
S.1	1	88	100	57	18	13	26	14	39	17,80	24	20
S.2	1	100	114	63	21	16	35	19	52	22,25	12	16
Type	Fig. No	Main Dimensions(mm)						Mechanical failing load	Power-frequency flashover voltage		Weight	Fired blank
		H	D	d	d1	d2	R		Dry	Wet		
ED-1	2	90	100	95	50	22	12	1200	22	10	0.75	WHITE
ED-2	2	75	80	75	42	20	10	1000	18	9	0.40	WHITE
ED-3	2	65	70	65	36	16	8	800	16	7	0.25	WHITE
ED-4	2	50	60	55	30	16	6	500	14	6	0.15	WHITE
ED-2(B)	3	76	89	83	48	21	10	1300			0.48	BROWN
ED-2(B)1	3	76	89	83	48	17.5	10	1300			0.50	BROWN
ED-2(C)	4	80	80		50	22	6	1350	25	12	0.47	BROWN