

Fig1




Fig2




Fig3




Fig4




Fig5

**ANA BOYUTLAR VE STANDART ÖZELLİKLER**

Sınıf ANSI	52-1 XP-4.5C-M	52-2 XP <sub>5</sub> -7C-E	52-3 XP-7-M	52-4 XP-7C-M	52-5 XP-11-M	52-6 XP-11C-M	52-8 XP-16-M	52-9 XP <sub>9</sub> -4.5C-E	52-10 XP 16C-E	
Fig.No	1	2	3	4	3	4	3	5	4	
Ana boyutlar (mm)	D	165	190.5	254	254	254	254	108	280	
	H	140	146	146	146	146	146	160	165	
Kaçak mesafesi / mm	178	210	292	292	292	292	320	171	280	
Güç frekansı delinme gerilimi kV	80	90	110	110	110	110	110	80	110	
Ortalama flashover Voltaj	Güç frekansı	Kuru / kV	60	65	80	80	80	80	60	80
		Islak / kV	30	35	50	50	50	50	30	50
	Kritik-İtici 15x40us Dalga	Pozitif / kV	100	115	125	125	125	125	125	100
		Negatif / kV	100	115	130	130	130	130	130	90
Radyo etkisi gerilimi	İçin voltajı test et toprak / kV	7.5	7.5	10	10	10	10	7.5	10	
	1000 kHz / kV'da maksimum RIV	50	50	50	50	50	50	50	50	
Anma E & M başarısız Yük / kN	45	70	70	70	111	111	160	45	160	
Gerilim geçirmez yük / kN	22	35.5	35.5	35.5	55.5	55.5	80	22	80	
Darbe etkisi / N. m	5	6	6	6	7	7	10	5	10	
Ağırlık (kg)	2.5	3.9	4.6	4.9	5.6	5.9	6.9	2.6	7.2	